

1/2"-Size



Spannung Voltage	120 V / 250 V	Strom Current	10 A / 15 A / 16 A	Type Type	Manuelle Rückstellung Manual Reset
----------------------------	----------------------	-------------------------	---------------------------	---------------------	--



Schaltzyklen / Switching cycles: 100.000 @ 10 A & 250V / 15 A & 120 V
30.000 @ 16 A & 250V

Anschluss / Connection: Flachstecker; 6,3 x 0,8 mm; Messing;
Oberfläche vernickelt; vertikal oder horizontal
Blade terminals; 6,3 x 0,8 mm; brass,
Surface nickel-plated; vertical or horizontal

Temperaturgrenzen des Schaltkopfes /
Temperature limits of the switch head: T_{min}: 0°C
T_{max}: +190°C

Befestigungsmöglichkeiten / Mounting options: Anlegeflansch / Docking flange
Topfflansch / Pot flange

Verpackungsmöglichkeiten / Packing options: 500 St. = lose geschüttet in Polybeutel /
500 pcs. = bulk in plastic bag

Bemessungswerte / Ratings:

Öffner - Anlegeflansch / Opener - Docking flange (Figure 1)		
Art. No.	Anschluss / Connection vertical	T _{open} (± 3°C) [°C]
36TXE26	611847	70
36TXE26	611889	80
36TXE26	611848	85
36TXE26	611888	90
36TXE26	611849	100
36TXE26	611890	110
36TXE26	611850	115
36TXE26	611891	120
36TXE26	611851	130
36TXE26	611892	140
36TXE26	611852	145
36TXE26	611893	150
36TXE26	611853	160
36TXE26	611894	170
36TXE26	611854	175

Öffner - Topfflansch / Opener - Pot flange (Figure 2)		
Art. No.	Anschluss / Connection vertical	T _{open} (± 3°C) [°C]
36TXE16	611855	70
36TXE16	611856	85
36TXE16	611857	100
36TXE16	611858	115
36TXE16	611859	130
36TXE16	611860	145
36TXE16	611861	160
36TXE16	611862	175

